

6. ATOMIC AND NUCLEAR PROPERTIES OF MATERIALS

Table 6.1. Revised May 2002 by D.E. Groom (LBNL). Gases are evaluated at 20°C and 1 atm (in parentheses) or at STP [square brackets]. Densities and refractive indices without parentheses or brackets are for solids or liquids, or are for cryogenic liquids at the indicated boiling point (BP) at 1 atm. Refractive indices are evaluated at the sodium D line. Data for compounds and mixtures are from Refs. 1 and 2. Further materials and properties are given in Ref. 3 and at <http://pdg.lbl.gov/AtomicNuclearProperties>.

Material	Z	A	(Z/A)	Nuclear ^a collision length λ_T {g/cm ² }	Nuclear ^a interaction length λ_I {g/cm ² }	$dE/dx _{\min}^b$ $\left\{ \frac{\text{MeV}}{\text{g/cm}^2} \right\}$	Radiation length ^c X_0 {g/cm ² }	Density {g/cm ³ } ({g/ℓ} for gas)	Liquid boiling point at 1 atm(K)	Refractive index n $((n - 1) \times 10^6$ for gas)
H ₂ gas	1	1.00794	0.99212	43.3	50.8	(4.103)	61.28 ^d (731000)	(0.0838)[0.0899]	[139.2]	
H ₂ liquid	1	1.00794	0.99212	43.3	50.8	4.034	61.28 ^d 866	0.0708	20.39	1.112
D ₂	1	2.0140	0.49652	45.7	54.7	(2.052)	122.4 724	0.169[0.179]	23.65	1.128 [138]
He	2	4.002602	0.49968	49.9	65.1	(1.937)	94.32 756	0.1249[0.1786]	4.224	1.024 [34.9]
Li	3	6.941	0.43221	54.6	73.4	1.639	82.76 155	0.534	—	
Be	4	9.012182	0.44384	55.8	75.2	1.594	65.19 35.28	1.848	—	
C	6	12.011	0.49954	60.2	86.3	1.745	42.70 18.8	2.265 ^e	—	
N ₂	7	14.00674	0.49976	61.4	87.8	(1.825)	37.99 47.1	0.8073[1.250]	77.36	1.205 [298]
O ₂	8	15.9994	0.50002	63.2	91.0	(1.801)	34.24 30.0	1.141[1.428]	90.18	1.22 [296]
F ₂	9	18.9984032	0.47372	65.5	95.3	(1.675)	32.93 21.85	1.507[1.696]	85.24	[195]
Ne	10	20.1797	0.49555	66.1	96.6	(1.724)	28.94 24.0	1.204[0.9005]	27.09	1.092 [67.1]
Al	13	26.981539	0.48181	70.6	106.4	1.615	24.01 8.9	2.70	—	
Si	14	28.0855	0.49848	70.6	106.0	1.664	21.82 9.36	2.33	3.95	
Ar	18	39.948	0.45059	76.4	117.2	(1.519)	19.55 14.0	1.396[1.782]	87.28	1.233 [283]
Ti	22	47.867	0.45948	79.9	124.9	1.476	16.17 3.56	4.54	—	
Fe	26	55.845	0.46556	82.8	131.9	1.451	13.84 1.76	7.87	—	
Cu	29	63.546	0.45636	85.6	134.9	1.403	12.86 1.43	8.96	—	
Ge	32	72.61	0.44071	88.3	140.5	1.371	12.25 2.30	5.323	—	
Sn	50	118.710	0.42120	100.2	163	1.264	8.82 1.21	7.31	—	
Xe	54	131.29	0.41130	102.8	169	(1.255)	8.48 2.87	2.953[5.858]	165.1	[701]
W	74	183.84	0.40250	110.3	185	1.145	6.76 0.35	19.3	—	
Pt	78	195.08	0.39984	113.3	189.7	1.129	6.54 0.305	21.45	—	
Pb	82	207.2	0.39575	116.2	194	1.123	6.37 0.56	11.35	—	
U	92	238.0289	0.38651	117.0	199	1.082	6.00 ≈0.32	≈18.95	—	
Air, (20°C, 1 atm.), [STP]			0.49919	62.0	90.0	(1.815)	36.66 [30420]	(1.205)[1.2931]	78.8	(273) [293]
H ₂ O			0.55509	60.1	83.6	1.991	36.08 36.1	1.00 373.15	—	1.33
CO ₂ gas			0.49989	62.4	89.7	(1.819)	36.2 [18310]	[1.977]	—	[410]
CO ₂ solid (dry ice)			0.49989	62.4	89.7	1.787	36.2 23.2	1.563	sublimes	—
Shielding concrete ^f			0.50274	67.4	99.9	1.711	26.7 10.7	2.5	—	
SiO ₂ (fused quartz)			0.49926	66.5	97.4	1.699	27.05 12.3	2.20 ^g	—	1.458
Dimethyl ether, (CH ₃) ₂ O			0.54778	59.4	82.9	—	38.89 —	—	248.7	—
Methane, CH ₄			0.62333	54.8	73.4	(2.417)	46.22 [64850]	0.4224[0.717]	111.7	[444]
Ethane, C ₂ H ₆			0.59861	55.8	75.7	(2.304)	45.47 [34035]	0.509(1.356) ^h	184.5	(1.038) ^h
Propane, C ₃ H ₈			0.58962	56.2	76.5	(2.262)	45.20 —	(1.879) [2.67]	231.1	—
Isobutane, (CH ₃) ₂ CHCH ₃			0.58496	56.4	77.0	(2.239)	45.07 [16930]	[2.67]	261.42	[1900]
Octane, liquid, CH ₃ (CH ₂) ₆ CH ₃			0.57778	56.7	77.7	2.123	44.86 63.8	0.703	398.8	1.397
Paraffin wax, CH ₃ (CH ₂) _{n≈23} CH ₃			0.57275	56.9	78.2	2.087	44.71 48.1	0.93	—	
Nylon, type 6 ⁱ			0.54790	58.5	81.5	1.974	41.84 36.7	1.14	—	
Polycarbonate (Lexan) ^j			0.52697	59.5	83.9	1.886	41.46 34.6	1.20	—	
Polyethylene terephthalate (Mylar) ^k			0.52037	60.2	85.7	1.848	39.95 28.7	1.39	—	
Polyethylene ^l			0.57034	57.0	78.4	2.076	44.64 ≈47.9	0.92–0.95	—	
Polyimide film (Kapton) ^m			0.51264	60.3	85.8	1.820	40.56 28.6	1.42	—	
Lucite, Plexiglas ⁿ			0.53937	59.3	83.0	1.929	40.49 ≈34.4	1.16–1.20	—	≈1.49
Polystyrene, scintillator ^o			0.53768	58.5	81.9	1.936	43.72 42.4	1.032	—	1.581
Polytetrafluoroethylene (Teflon) ^p			0.47992	64.2	93.0	1.671	34.84 15.8	2.20	—	
Polyvinyltoluene, scintillator ^q			0.54155	58.3	81.5	1.956	43.83 42.5	1.032	—	
Aluminum oxide (Al ₂ O ₃)			0.49038	67.0	98.9	1.647	27.94 7.04	3.97	—	1.761
Barium fluoride (BaF ₂)			0.42207	92.0	145	1.303	9.91 2.05	4.89	—	1.56
Bismuth germanate (BGO) ^r			0.42065	98.2	157	1.251	7.97 1.12	7.1	—	2.15
Cesium iodide (CsI)			0.41569	102	167	1.243	8.39 1.85	4.53	—	1.80
Lithium fluoride (LiF)			0.46262	62.2	88.2	1.614	39.25 14.91	2.632	—	1.392
Sodium fluoride (NaF)			0.47632	66.9	98.3	1.69	29.87 11.68	2.558	—	1.336
Sodium iodide (NaI)			0.42697	94.6	151	1.305	9.49 2.59	3.67	—	1.775
Silica Aerogel ^s			0.50093	66.3	96.9	1.740	27.25 136@ρ=0.2	0.04–0.6	—	1.0+0.21ρ
NEMA G10 plate ^t				62.6	90.2	1.87	33.0 19.4	1.7	—	

Material	Dielectric constant ($\kappa = \epsilon/\epsilon_0$) () is $(\kappa-1) \times 10^6$ for gas	Young's modulus [10^6 psi]	Coeff. of thermal expansion [10^{-6} cm/cm \cdot °C]	Specific heat [cal/g·°C]	Electrical resistivity [$\mu\Omega\text{cm}(@^\circ\text{C})$]	Thermal conductivity [cal/cm·°C·sec]
H ₂	(253.9)	—	—	—	—	—
He	(64)	—	—	—	—	—
Li	—	—	56	0.86	8.55(0°)	0.17
Be	—	37	12.4	0.436	5.885(0°)	0.38
C	—	0.7	0.6–4.3	0.165	1375(0°)	0.057
N ₂	(548.5)	—	—	—	—	—
O ₂	(495)	—	—	—	—	—
Ne	(127)	—	—	—	—	—
Al	—	10	23.9	0.215	2.65(20°)	0.53
Si	11.9	16	2.8–7.3	0.162	—	0.20
Ar	(517)	—	—	—	—	—
Ti	—	16.8	8.5	0.126	50(0°)	—
Fe	—	28.5	11.7	0.11	9.71(20°)	0.18
Cu	—	16	16.5	0.092	1.67(20°)	0.94
Ge	16.0	—	5.75	0.073	—	0.14
Sn	—	6	20	0.052	11.5(20°)	0.16
Xe	—	—	—	—	—	—
W	—	50	4.4	0.032	5.5(20°)	0.48
Pt	—	21	8.9	0.032	9.83(0°)	0.17
Pb	—	2.6	29.3	0.038	20.65(20°)	0.083
U	—	—	36.1	0.028	29(20°)	0.064

1. R.M. Sternheimer, M.J. Berger, and S.M. Seltzer, Atomic Data and Nuclear Data Tables **30**, 261–271 (1984).
 2. S.M. Seltzer and M.J. Berger, Int. J. Appl. Radiat. **33**, 1189–1218 (1982).
 3. D.E. Groom, N.V. Mokhov, and S.I. Striganov, “Muon stopping-power and range tables,” Atomic Data and Nuclear Data Tables **78**, 183–356 (2001).
 4. S.M. Seltzer and M.J. Berger, Int. J. Appl. Radiat. **35**, 665 (1984) & <http://physics.nist.gov/PhysRefData/Star/Text/contents.html>.
- a. σ_T , λ_T and λ_I are energy dependent. Values quoted apply to high energy range, where energy dependence is weak. Mean free path between collisions (λ_T) or inelastic interactions (λ_I), calculated from $\lambda^{-1} = N_A \sum w_j \sigma_j / A_j$, where N_A is Avogadro’s number and w_j is the weight fraction of the j th element in the element, compound, or mixture. σ_{total} at 80–240 GeV for neutrons ($\approx \sigma$ for protons) from Murthy *et al.*, Nucl. Phys. **B92**, 269 (1975). This scales approximately as $A^{0.77}$. $\sigma_{\text{inelastic}} = \sigma_{\text{total}} - \sigma_{\text{elastic}} - \sigma_{\text{quasielastic}}$; for neutrons at 60–375 GeV from Roberts *et al.*, Nucl. Phys. **B159**, 56 (1979). For protons and other particles, see Carroll *et al.*, Phys. Lett. **80B**, 319 (1979); note that $\sigma_I(p) \approx \sigma_I(n)$. σ_I scales approximately as $A^{0.71}$.
- b. For minimum-ionizing muons (results are very slightly different for other particles). Minimum dE/dx from Ref. 3, using density effect correction coefficients from Ref. 1. For electrons and positrons see Ref. 4. Ionization energy loss is discussed in Sec. 27.
- c. From Y.S. Tsai, Rev. Mod. Phys. **46**, 815 (1974); X_0 data for all elements up to uranium are given. Corrections for molecular binding applied for H₂ and D₂. For atomic H, $X_0 = 63.05 \text{ g/cm}^2$.
- d. For molecular hydrogen (deuterium). For atomic H, $X_0 = 63.047 \text{ g cm}^{-2}$.
- e. For pure graphite; industrial graphite density may vary 2.1–2.3 g/cm³.
- f. Standard shielding blocks, typical composition O₂ 52%, Si 32.5%, Ca 6%, Na 1.5%, Fe 2%, Al 4%, plus reinforcing iron bars. The attenuation length, $\ell = 115 \pm 5 \text{ g/cm}^2$, is also valid for earth (typical $\rho = 2.15$), from CERN-LRL-RHEL Shielding exp., UCRL-17841 (1968).
- g. For typical fused quartz. The specific gravity of crystalline quartz is 2.64.
- h. Solid ethane density at -60°C ; gaseous refractive index at 0°C , 546 mm pressure.
- i. Nylon, Type 6, $(\text{NH}(\text{CH}_2)_5\text{CO})_n$
- j. Polycarbonate (Lexan), $(\text{C}_{16}\text{H}_{14}\text{O}_3)_n$
- k. Polyethylene terephthalate, monomer, C₅H₄O₂
- l. Polyethylene, monomer CH₂=CH₂
- m. Polymide film (Kapton), $(\text{C}_{22}\text{H}_{10}\text{N}_2\text{O}_5)_n$
- n. Polymethylmethacrylate, monomer CH₂=C(CH₃)CO₂CH₃
- o. Polystyrene, monomer C₆H₅CH=CH₂
- p. Teflon, monomer CF₂=CF₂
- q. Polyvinyltoluene, monomer 2-CH₃C₆H₄CH=CH₂
- r. Bismuth germanate (BGO), $(\text{Bi}_2\text{O}_3)_2(\text{GeO}_2)_3$
- s. 97% SiO₂ + 3% H₂O by weight; see A. R. Buzykaev *et al.*, Nucl. Instrum. Methods **A433**, 396 (1999). Aerogel in the density range 0.04–0.06 g/cm³ has been used in Čerenkov counters, but aerogel with higher and lower densities has been produced. ρ = density in g/cm³.
- t. G10-plate, typically 60% SiO₂ and 40% epoxy.